

**Amendments to the Claims:**

The following listing of claims will replace all prior versions, and listings of claims in the application:

1. (Currently Amended) A composite anchor comprising:  
a first anchor bolt installed projecting outside of a concrete frame;  
~~and~~ a second anchor bolt ~~which~~ that is eccentrically positioned to the axis of ~~said the~~  
first anchor bolt; and  
a connecting part for connecting ~~said the~~ first and the second anchor bolts,  
wherein ~~said the~~ connecting part ~~is provided with projecting portion which projects in~~  
~~the opposite direction to the first anchor bolt~~ extends radially from the first anchor bolt to and  
past the second anchor bolt,

the second anchor bolt being located in a radial center of the connecting part, thereby  
reducing the bending moment which is exerted locally on the connecting part due to a load on  
~~said the~~ first anchor bolt.

2. (Currently Amended) A composite anchor bolt according to claim 1, wherein  
the planar configuration of ~~said the~~ connecting part is made to be a polygonal or circular  
shape, thereby increasing the compressive force transfer area of ~~said the~~ projecting portion.

3. (Currently Amended) A composite anchor bolt according to claim 1, wherein  
~~said the~~ connecting part is formed to have top and bottom surfaces of a polygonal or circular  
shape, and ~~said the~~ second anchor bolt is positioned at the center of the connecting part.

4. (Currently Amended) A composite anchor bolt according to claim 1, wherein  
~~said the~~ connecting part has an injection hole for the adhesive and an air hole.

5. (Currently Amended) A composite anchor bolt according to claim 1, wherein  
both of ~~said the~~ first anchor bolt and ~~said the~~ second anchor bolt are formed with the same or  
different diameters.

6. (Currently Amended) A composite anchor bolt according to claim 1, wherein  
~~said the~~ second anchor bolt has a larger diameter than ~~said the~~ first anchor bolt, and formed  
with a shorter length in the embedded concrete.

7. (Currently Amended) A composite anchor bolt comprising:  
a first anchor bolt installed projecting outside of the concrete frame;  
a second anchor bolt which is eccentrically positioned to the axis of ~~said the~~ first anchor bolt; and  
a connecting part for connecting ~~said the~~ first and the second anchor bolts,  
wherein the center of ~~said the~~ connecting part and the axis of the ~~first anchor bolt are~~ coaxial, ~~a planar configuration of said connecting part is formed in a polygonal or circular shape, and said second anchor bolt can be selectively positioned in a certain circumference.~~  
second anchor bolt are coaxial, and

a planar configuration of the connecting part is formed in a polygonal or circular shape, and the first anchor bolt is positioned toward a radial edge of the connecting part.

8. (Currently Amended) A composite anchor bolt according to claim 7, wherein the planar configuration of ~~said the~~ connecting part is made either a circular, triangular, quadrangular, or polygonal configuration to increase the adhesive area of the composite anchor bolt with the concrete.

9. (Currently Amended) A composite anchor bolt according to claim 7, wherein a reinforcing portion is formed at a joining point between ~~said the~~ second anchor bolt and ~~said the~~ connecting part to compensate for a bending moment which is exerted locally on the joining point.

10. (Currently Amended) A composite anchor bolt according to claim 7, wherein of both ~~said the~~ first anchor bolt and ~~said the~~ second anchor bolt are formed with the same or different diameters.

11. (Currently Amended) A composite anchor bolt according to claim 7, wherein ~~said the~~ second anchor bolt has a large diameter than that of ~~said the~~ first anchor bolt, and formed with a shorter length in the embedded concrete.

12. (Currently Amended) A composite anchor bolt according to claim 7, wherein ~~said the~~ connecting part has an injection hole for the adhesive and an air hole.

13. (Currently Amended) A composite anchor bolt according to claim 7, wherein at least one of ~~said-the~~ first anchor bolt and second anchor bolt is removably attachable to ~~said~~ the connecting part.

14. (Currently Amended) A composite anchor bolt comprising:  
a first anchor bolt installed projecting outside of the concrete frame;  
a second anchor bolt which is eccentrically positioned to the axis of ~~said-the~~ first anchor bolt; and  
a connecting part for connecting the first and the second anchor bolts,  
wherein ~~said-the~~ connecting part and second anchor bolt are formed together in a T-shape configuration, and ~~said-the~~ first anchor bolt is placed at the end side of the connecting part.

15. (Currently Amended) A composite anchor bolt according to claim 14, wherein at least one of ~~said-the~~ first anchor bolt and second anchor bolt is removably attachable to ~~said~~ the connecting part.

16. (Currently Amended) ~~The~~ A method of installing a composite anchor bolt comprising:  
preparing a composite anchor bolt ~~which comprises including~~ a first anchor bolt and a second anchor bolt positioned eccentrically in a direction perpendicular to each other bolt projecting on the outside and a second anchor bolt positioned eccentrically to the first anchor bolt, with a planar connecting part connecting the first and second anchor bolts; bolts,  
the first anchor bolt projecting on the outside of a matrix in which the composite anchor bolt is embedded and a second anchor bolt positioned eccentrically to the first anchor bolt relative to the planar connecting part projecting inside the matrix;  
removing a cylindrical or polygonal core from the reinforcement covering margin to confirm the position of the reinforcement within the matrix,  
when reinforcement is encountered in the anchor borehole position, ~~said-the~~ core corresponding to the shape of ~~said-the~~ connecting part, and surrounding the borehole;  
drilling a borehole for ~~said-the~~ second anchor bolt; and  
jointly attaching ~~said-the~~ composite anchor ~~bolt; bolt,~~

wherein the connecting part extends radially from the first anchor bolt to and past the second anchor bolt.

17. (Currently Amended) The method of installing a composite anchor bolt according to claim 16, wherein after the second anchor bolt is set into the drilled borehole, the adhesive is injected into an adhesive injection hole which is formed in ~~said~~the connecting part, air is released from an air hole which is formed in ~~said~~the connecting part, and ~~said~~the composite anchor bolt is attached.

18. (Currently Amended) The method of installing a composite anchor bolt according to claim 16, wherein a portion of ~~said~~the connecting part is projected outside from the concrete frame, and an equipment base is placed on ~~said~~the connecting part and attached with ~~said~~the first anchor bolt.